

ReTac®

Textures

ReTac® Textures can add depth and visual appeal to static, flat images with its embossed canvas finish. With ReTac® on the back, eye-catching graphics printed on ReTac® Textures can easily be removed and repositioned multiple times without the worry of adhesive residue being left behind. This phthalate-free film can be easily applied, re-positioned and removed without surface damage or loss of adhesion. Available in Canvas, Linen, Sand and Woodgrain finishes.

- IDEAL FOR INTERIOR PROMOTIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

6 mil White Phthalate-Free Polymeric PVC



Matte



(Eco) Solvent
Latex
UV



ReTac® ultra removable
and re-positionable
adhesive



Widths up to 54 in



INTERIOR AND EXTERIOR
(2 YEAR REMOVABILITY EXTERIOR)

ADDS VISUAL INTEREST TO ANY PRINT

WOODGRAIN

LINEN

CANVAS

SAND

APPLICATIONS

Smooth Flat Surfaces
Point Of Sale Graphics
Interior Décor
Decals & Stickers

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Textures

ReTac® Textures is a 150µ (6 mil) printable, matte white phthalate-free polymeric PVC film with ReTac® ultra removable adhesive. It has an embossed finish that adds depth and visual appeal to static, flat graphics. The texture helps draw attention to your image or message in a distinct and creative way.

- RETAC® TEXTURES IS A PHTHALATE-FREE FILM.
- IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE, AND TEXTURED LABELS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.


07082019

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

PRODUCT CHARACTERISTICS

Film Thickness	6 mil (150μ)		
Adhesive Layer	1 mil (25μ)		
Outdoor Durability	5 years; 2 years removability		
Fire Rating	Class C-s1-d0 (EN-13501) Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)		
Application Temperature	>41°F (5°C)		
Service Temperature Range	-40°F to 120°F (-4.4°C to 48.9°C)		
Shelf Life	2 years		
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity		

INSTALLATION RECOMMENDATION

Please see Wall Graphic Installation & Removal Instructions for further details. The surface must be clean and smooth and free of defects before application.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013