

Low VOC Cleaner

6405SP

6405SP is a 0.4 VOC Wax and Grease Remover. 6405SP is compliant with all VOC rules nationwide.

6405SP is specifically designed to remove waxes, grease, silicones, and other contaminants. It can be used on bare metal, plastics, primers, etc.



Features:

- Low VOC
- Universal

Benefits:

- Compliant Nationwide
- Cleans all Substrates

Directions for Use

6405SP 0.4 VOC Cleaner:



- Apply a generous amount of **6405SP** to a clean cloth or directly to the surface.
- The initial application will float contaminants to the surface, and the second wipe using a separate clean dry cloth, will remove contaminants.
- For maximum results, wipe the surface dry while it is still wet, using a clean white cloth in one direction. This will eliminate the smearing of contaminants. Be sure to change rags frequently.
- Never let the cleaner dry on the surface.
- Use **6405SP** before and after sanding.

Technical Data:

Color	Clear
VOC lbs./US gal.	0.41 VOC
Weight Per US gal.	8.37 lbs./gal.
Flash Point PMCC	> 200°F

6405SP

Low VOC Cleaner

Important:

Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; MEXICO 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



MATTHEWS PAINT

The World's Finest Coating For Architectural Signage

760 Pittsburgh Drive
Delaware, OH 43015
Toll Free: 800/323-6593
Toll Free FAX: 800/947-0377