

**PLASTIC PREP**

# 6428SP

Matthews 6428SP Plastic Prep is a multi use product developed as an anti-static agent, a plastic parts cleaner, and as a cleaner for mold release agents.

6428SP Plastic Prep is ready to use as packaged.



Features:	Advantages:	Benefits:
<ul style="list-style-type: none"> <li>· 3 In 1 Product</li> <li>· Anti-Static Agent</li> </ul>	<ul style="list-style-type: none"> <li>· Versatile</li> <li>· Easy to Apply</li> </ul>	<ul style="list-style-type: none"> <li>· Less Inventory</li> <li>· Cleaner Paint Jobs</li> </ul>
Directions for Use		
<b>Anti Static Agent:</b>	Using a spray gun or mist bottle, apply a mist coat of 6428SP on the surface to be painted. This will help reduce static electricity on all treated surfaces, minimizing the attraction of dust & dirt particles.	
<b>Cleaner for Plastics and Flexible Parts:</b>	6428SP quickly removes troublesome silicones and mold release agents from the substrate to be painted. Saturate a clean white cloth, wipe in one direction only, and immediately dry with a clean cloth. Use 6428SP before and after sanding. <b>Caution:</b> Do not wipe over sensitive substrates such as fresh topcoats and/or primers as softening may occur.	
Technical Data:	Color VOC LB/US gal Weight Per US gal. Flash Point PMCC	Clear 6.5 6.6 53°F
<b>Important:</b>	Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.	

# 6428SP

**PLASTIC PREP**

---

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

---

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; MEXICO 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein.

If you require technical assistance, please call us toll-free 800/323-6593.



**MATTHEWS PAINT**

*The World's Finest Coating For Architectural Signage*

760 Pittsburgh Drive  
Delaware, OH 43015  
Toll Free: 800/323-6593  
Toll Free FAX: 800/947-0377